




PASCO VALVES INTERNATIONAL



**GATE/GLOBE/CHECK VALVE, BALL VALVES, BUTTERFLY VALVES,
KNIFE GATE VALVES, CONTROL VALVES and ACTUATION**



**CARBON STEEL, STAINLESS STEEL, HASTELLOY, CARPETER 20
MONEL, PVC, CAST IRON, DUCTILE IRON, TITANIUM, DUPLEX**



3 PC FOUR BOLT
1000 PSI BALL VALVE
CONNECTION TYPE:
NPT, SOCKET
SIZES: 1/2" - 4"
MATERIAL: CARBON,
STAINLESS STEEL



3-PC 4 BOLT CONCEALED
2000 PSI BALL VALVE
CONNECTION TYPE:
COMPRESSION
SIZES: 1/4" - 1"
MATERIAL: CARBON/
STAINLESS



2PC-THREADED END
3000 PSI BALL VALVE
CONNECTION TYPE:
THREADED END
SIZES: 1/4" - 2"
MATERIAL:
CARBON STEEL,STAINLESS



3PC - FOUR BOLT
CONNECTION TYPE:
THREADED END, SOCKET
WELD, BUTT WELD
SIZES: 1/2" - 4"
MATERIAL: CARBON
STEEL,STAINLESS



DIRECT MOUNT DESIGN
CONNECTION TYPE:
THREADED,SOCKET WELD
SIZES: 1/2" - 4"
MATERIAL: CARBON,
STAINLESS STEEL



SANITARY STYLE VALVE
CONNECTION TYPE:
POLISHED TRI CLAMP
SIZES: 1/2" - 4"
MATERIAL: STAINLESS
STEEL W/ CAVITY FILLER



3WAY NPT T or L PORT
CONNECTION TYPE:
THREADED, soa<ET AND
BUTT WELD ENDS
SIZES: 1/4" - 2"
MATERIAL: CARBON /
STAINLESS STEEL




3WAY FLANGED BALL VALVE
DIRECT MOUNT DESIGN
FULL & STANDARD PORT
SIZES: 1/2" - 6"
MATERIAL :
CARBON/STAINLESS
ANSI 150,300,600#



INDUSTRIAL VALVE SERIES
CONNECTION TYPE: UNION
NPT & SOCKET WELD
SIZES: 1/4" - 2"
MATERIAL: STAINLESS STEEL,
TEFLON
3PC WITH MOUNTING PAD



TRUNNION MOUNTED
CONNECTION TYPE:
TRUNNION END
SIZES: 8" - 24"
MATERIAL : CARBON /
STAINLESS STEEL,
SPECIALTY ALLOYS



METAL SEATED VALVE
CONNECTION TYPE:
ANSI 150-600#RF FLANGED
SIZES: 1/2" - 6"
MATERIAL: CARBON /
STAINLESS STEEL



2PC FULL PORT VALVES
CONNECTION TYPE:
ANSI 150-600#RF FLANGED
SIZES:1/4"-6"
MATERIAL: CARBON/
STAINLESS STEEL
FIRE SAFE APPROVAL



RESILIENT SEATED, WAFER/LUG
 SIZES: 2"-24". 26" - 40"
 MATERIAL: DUCTILE IRON/
 CARBON AND STAINLESS STEEL



INDUSTRIAL SPLIT BODY BUTTERFLY
 ONE-PIECE DISC/STEM DESIGN
 BI-DIRECTIONAL "U" QJP STEM SEAL
 SIZES: 2"-24"
 MATERIAL: SS, CAST IRON, BUNA/
 EPOXY, TFE LINED



DOUBLE OFFSET ECCENTRIC
 HIGH PERFORMANCE WAFER/LUG
 DIRECT MOUNT FOR ACTUATORS
 SIZES: 2"-24"
 MATERIAL: STAINLESS STEEL OR
 CARBON STEEL, OPTIONAL
 SEATS



ACTUATED DOUBLEOFFSET BUTTERFLY
 LUG & WAFER STYLES
 HEAVY DUTY ONE-PIECE BODY
 SIZES: 2"-24", ANSI 150-300
 MATERIAL: CARBON/STAINLESS



3 WAY DIVERTING BUTTERFLY
 LUG & WAFER STYLES
 DESIGN SIZES: 2"-24"
 TRIM MATERIAL: STAINLESS
 STEEL



3 WAY TYPE L - T PORT VALVES
 BI-DIRECTIONAL
 ANSI 150-600#RF FLANGED
 SIZES: 2"-24" MATERIAL:
 CARBON/STAINLESS STEEL



**HIGH PERFORMANCE TRIPLE OFFSET
 METAL SEATED/ SOFT SEATED**
 ZERO LEAKAGE AND TIGHT SHUT-OFF
 TRIPLE ECCENTRIC DESIGN
 SIZES: 3"-24"
 MATERIAL: CARBON/ STAINLESS
 STEEL LUG/WAFER BODIES



PLASTIC BUTTERFLY BALL VALVES
 WAFER/ FLANGED / LUG BODIES/NPT
 SIZES: 2 " - 24"
 MATERIAL: PVC, CPVC, PVDF, PP



MOUNTING HARDWARE/PARTS
 FOR ALL SIZES -STOCK
 ISO / FABRICATED BRACKETS
 CNC PROCESSED
 NAMUR BRACKETS
 MADE WITH STAINLESS STEEL

PASCO V-PORT BALL VALVES



V-PORT BALL VALVES

- * SERIES V-PORT BALL VALVES ARE IDEAL FOR ACHIEVING MORE PRECISE CONTROL
- * METAL /SOFT SEATSEALING FEATURES OF A BALL VALVE
- * WE OFFER V-PORT BALL VALVES 1/2" - 4" - ALSO IN A 3-PIECE DESIGN AND 1/2"- 24" ANSI 150# FLANGED.
- * THE STANDARD "V" NOTCH OPTIONS ARE 30 °, 60 ° & 90 ° .




PVC V-PORT BALL VALVE

- * 1/2 - 12" INDUSTRIAL PVCV-PORT BALL VALVES SIZES AVAILABLE
- * THE STANDARD "V" NOTCH OPTIONS ARE 30 °, 60 ° & 90 °
- * V-PORT BALL VALVES OFFER BETTER AND MORE CONSISTENT FLOW
- * AVAILABLE IN PVC, CPVC, PVDF AND PP
- * ACTUATED PNEUMATICALLY OR ELECTRICALLY



SERIES 3-4 WAY V-PORT

- * 1/2" - 4" INDUSTRIAL DIRECT MOUNT MULTI-PORT STANDARD AND V-PORT BALL VALVES SIZES AVAILABLE
- * ISO 5211 DIRECT MOUNT PAD. ALLOWS DIRECT MOUNTING OF PNEUMATIC AND ELECTRIC ACTUATORS
- * FULL PORT, MULTI PORT DESIGN, L & T PORT FLOW DESIGN



SEGMENTED BALL VALVES

- * HIGH RANGEABILITY - 300:1 TURN DOWN RATIO
- * V-PORT OR SEGMENTED BALL VALVE
- * EQUAL PERCENTAGE FLOW CHARACTERISTIC
- * LOW PRESSURE RECOVERY RATE - MINIMIZES CAVITATION AND EXCESSIVE NOISE
- * MULTI-BODY RATING ANSI 150/300
- * EPOXY LINED FOR SEVERE SERVICE APPLICATIONS



PROCESS CONTROL VALVES
 SINGLE SEATED OR CAGE GUIDED
 SIZES: 1/2" - 2" NPT
 SIZES : 1 - 8" ANSI 150-600#RF
 MATERIAL: CARBON OR STAINLESS
 FIELD REVERSIBLE ACTUATORS



**FUSIBLE LINK AUTOMATIC CLOSURE
 IN CASE OF FIRE**
 AVAILABLE IN ANSI FLANGES
 API 607 FIRE SAFE VALVE
 SIZES: 1/2" - 4"
 HEAVY-DUTY SOLDERED FUSIBLE LINKS



GATE, GLOBE, CHECK VALVES
 FLANGED, THREADED OR SOCKET
 AVAILABLE IN VARIOUS SIZES AND
 IN VARIOUS MATERIALS
 ANSI 150-1500#RF FLANGED



KNIFE GATE VALVES
 SLURRY, SLUETH OR CONTROL
 METAL OR SOFT SEAT
 FULL FACE FLANGE
 SIZES: 2"-24"
 MATERIAL: CARBON/STAINLESS STEEL



PLUG VALVES SLEEVED OR LINE
 SIZES: 2"-24"
 AVAILABLE IN VARIOUS MATERIALS
 AND LINERS



HIGH QUALITY PVC VALVES
 BALL VALVES, BUTTERFLY VALVES
 AND V-PORT BALL VALVES
 SIZES: 1"-12"
 ECONOMIC VALVE OIICE



SAFETY RELIEF VALVES
 SECTION VIII
 SIZES: 1"-12" ANSI 150-900#RF
 MATERIAL: CARBON/STAINLESS
 STEEL



SANITARY PROCESS VALVES
 BALL, BUTTERFLY, 3 WAY
 AIR AND ELECTRIC ACTUATORS
 ARE ALSO AVAILABLE
 SIZES: 1/2" - 6"
 MATERIAL: STAINLESS STEEL



SOLENOID VALVES
 DIRECT AND PILOT OPERATED
 SIZE: 1/4" - 8"
 MATERIAL: IRON, STAINLESS
 STEEL AND BRASS



NTQ ELECTRIC ACTUATOR
 OPEN/CLOSE & MODULATING
 EFFICIENT, LOW POWER,
 DC MOTORS AVAILABLE
 MANUAL OVERRIDE
 IP65 AND EXPLOSION PROOF

ELECTRIC ACTUATOR
 ELECTRIC MOTOR: 120VAC
 RANGE: -31 °F TO + 150°F
 OVERLOAD PROTECTION
 MANUAL HANDLE OVERRIDE
 CE, NEMA 4X

NTQ SERIES ELECTRIC ACTUATOR



SMART IQ ELECTRIC ACTUATOR

INTEGRAL AUXILIARY SWITCH
 REVERSIBLE MOUNTING
 SIMPLIFY FIELD WIRING
 ELECTRONIC STALL
 DETECTION
 MANUAL OVERRIDE, HIGH
 TORQUES



NTE ELECTRIC ACTUATOR

IP 67 AND 68
 DETACHABLE CRANK
 HANDLE
 18 TO 6000NM TORQUE
 90 - 180 Deg rotations



SERIES NSF SCOTCH YOKE

TORQUE FROM 978Nm to
 226,200Nm
 ISO 5211, PNEUMATIC OR
 HYDRAULIC, DOUBLE
 ACTING & SPRING RETURN

**NK Series Rack & Pinion
 Pneumatic Actuator**



NK PNEUMATIC RACK & PINION

NAMUR MOUNT, ISO 5211
 90-180 Deg with INDICATOR
 ANODIZED, COATED, STAINLESS
 AND PLASTIC, DOUBLE ACTING
 & SPRING RETURN



LIMIT SWITCHES

POLYCARBONATE DOME
 1/2" CONDUIT ENTRIES
 WEATHER PROOF
 ALUMINUM
 OR PLASTIC
 IP65/68, EXPLOSION
 PROOF
 CE, ATEX, ULC, ROHS



LIMIT SWITCH

INDUCTIVE PROXIMITY
 TOP MOUNTED POSITION
 INDICATED-ECONOMICAL
 IP65/68, EXPLOSION PROOF
 CE, ATEX, ULC, ROHS



DOUBLE ACTING & SPRING RETURN

TOP QUALITY BEARINGS
 HARD ANODIZED EXTRUDED
 ALUMINUM BODY
 METAL SPRING GUIDES LOW
 FRICTION/HIGH LIFE



STAINLESS STEEL PNEUMATIC

HEAVY-DUTY PINION
 SPRING CARTRIDGES
 All SS HOUSING
 DIRECT MOUNTING
 ISO 5211



POSITIONERS

ROTARY OR LINEAR
 SPLIT RANGE AVAILABLE
 VIBRATION RESISTANT
 STAINLESS STEEL GAUGES
 CE, ATEX, ULC, ROHS



DECLUTCHABLE GEARBOX

VALVES & ACTUATORS
 SMALL & LIGHT WEIGHT
 TWO KEY WAYS
 WIDE RANGE OF SIZES



**ACTUATED VALVES
PNEUMATIC -ELECTRIC**
DIRECT MOUNT FOR
LOW-PROFILE OR
BRACKET MOUNT



PNEUMATIC ACTUATORS
RACK N PINION
MATERIAL: ANODIZED ALUMINUM,
STAINLESS OR PLASTIC



**ELECTRIC ACTUATORS FOR
OS&Y GATES AND GLOBE
VALVES**
SMART ELECTRONICS WITH
MANUAL OVERRIDES
SIZES: 1/2"- 12" ANSI 150/1500#
MATERIAL: CARBON/STAINLESS



**PNEUMATIC OR ELECTRIC
KNIFEGATES**
DIRECT INTEGRAL POSITIONERS
SIZES: 2" - 40"
MATERIALS: DUCTILE IRON,
CARBON / STAINLESS AND
SPECIALTY ALLOYS



PNEUMATIC OR ELECTRIC 3 WAYS
MIXING AND DIVERTING
SIZES: 1/2" - 12"ANSI 150-300#RF
MATERIAL: CARBON/STAINLESS AND
SPECIALTY ALLOYS



**PNEUMATIC / ELECTRIC CONTROL
LINEAR GLOBE CONTROL**
STEM GUIDED , CAGED TRIMS,
SPECIALTY TRIM FOR NOISE
SIZES: 1/2" - 12"ANSI 150-1500#RF
MATERIALS: DUCTILE IRON, CARBON/
STAINLESS AND SPECIALTY ALLOYS



PNEUMATIC / ELECTRIC ACTUATORS
PVC, CPVC OR PVDF FLANGED ENDS
SIZES: 1/2" - 12"



LINED CONTROL VALVES
TEFLON LINED ANSI 150# RF
SIZES: 1/2" - 4"
DUCTILE IRON BODIES



**PNEUMATIC OR ELECTRIC
CONTROL BALL VALVES**
SIZES: 2" - 24"
MATERIALS: CARBON,
STAINLESS, SPECIALTY ALLOYS

SUPPLIES:

- FULL PORT BRASS BALL VALVES
- 3-WAY BRASS BALL VALVES
- FULL PORT STAINLESS STEEL BALL VALVES
- 3-PC STAINLESS STEEL BALL VALVES
- SS SANITARY TRI-CLAMP BALL VALVES
- STAINLESS STEEL FLANGED VALVES
- PVC/CPVC BALL VALVES
- 3-WAY PVC BALL VALVES
- BUTTERFLY VALVES, WAFER & LUG STYLE
- TRIPLE OFFSET BUTTERFLY VALVES
- PNEUMATIC ACTUATORS
- ELECTRIC ACTUATORS
- LIMIT SWITCHES
- VALVE POSITIONERS
- GEAR OVERRIDES
- LOCKOUTS
- PILOT VALVES
- MOUNTING KITS
- I/P TRANSDUCERS
- SLUICE GATES
- SOLENOID VALVES
- INDUSTRIAL VALVES
- BALL VALVES
- BUTTERFLY VALVES
- KNIFE GATE VALVES
- PLUG VALVES
- SANITARY VALVES
- SAFETY RELIEF
- PVC VALVES
- V-PORT BALL VALVES



Petrochemical



Chemical



Mining



Power Generation

PASCO is an international supplier of valves, controls and actuation worldwide. Supplying the major industries with high quality, competitive products with good lead times. Having a diversified line to allow customers to consolidate their various requirements. Backed by 30 years experience and extensive knowledge and understanding of industrial applications. We can meet the most demanding requirements including all special alloys and designs.

“IF YOU NEED IT WE HAVE IT”



**100 Lancing Drive
Unit #5
Hamilton, Ontario
L8W 3L6**

CONTACT US TODAY

Toll Free: 1-855-855-0926

Phone: 289-335-0331

Email: sales@pascovalves.com

Web: www.pascovalves.com